


Material:

- Cable: USB1.1 E189529 UL2725 28#/1P+24#/2C+AEB
 - OD 4.7MM
 - Beige (IV-29#)
- P1 Connector: USB A Male Shell
 - Pin G/F
 - 4PCS Type
 - Insulator color: white
 - Shell Plate Nickel
- P2 Connector: USB A Male Shell
 - Pin G/F
 - 3PCS Type
 - Insulator color: white
 - Shell Plate Nickel
- Outer Jacket: Beige (IV-29#) PVC-40P
- 80°C 30V VW-1

PIN Assignment:

P1		P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
SHELL DRAIN+BRAID		SHELL



1PC / PE Bag

Electrical:

- 100% short, open, miswire test
- Conduct resistance: 2Ω Max.
- Insulation resistance: 5MΩ Min.
- Dielectric test: 300V DC



Scale	1:1						Name	Item No.
TOLERANCE						Drawn	01.04.12	AK672-5
X.X	±0.40					Approved		
X.XX	±0.25							Title
X.XXX	±0.15							USB 1.1 Cable - A Male <=> B Male, Beige, 5 Meters
Angle	±3°							Drawing No.
								Replace
								Sheet
		Modification	Date	Name				



	rev00