

154-00500

Article Number: 154-00500

Description: Cable Tie Mounting Plates, .50" x 4.25", T18-T50 Cable Ties, #10 (M5) Screw, PA66, Natural, 100/pk



| Base Data                           |  |
|-------------------------------------|--|
| Local Order Number                  | MP3M5.NN3P   |
| Type                                | MP3M5  |
| Color                               | Natural (NA)   |
| Features and Benefits               | <ul style="list-style-type: none"> <li>• Mounting plates allow multiple bundles to run parallel.</li> <li>• The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.</li> </ul> |
| Quantity Per                        | bag  |
| Product Description                 | HellermannTyton mounting plates allow multiple cable to be run in parallel. The mount is secured with two screws and the cables are attached to the plate by using a cable tie through any of the available slots.                             |
| Short Description                   | Cable Tie Mounting Plates, .50" x 4.25", T18-T50 Cable Ties, #10 (M5) Screw, PA66, Natural, 100/pk   |
| Product Dimensions                  |  |
| Length L (Imperial)                 | 4.25"  |
| Length L (Metric)                   | 108.0mm  |
| Fixation Method                     | Screw Mounting and Rivet   |
| Number of Bundles                   | 3  |
| Width W (Imperial)                  | 0.5"   |
| Width W (Metric)                    | 12.7mm   |
| Cable Tie Width Max. (Imperial)     | 0.2"   |
| Cable Tie Width Max. (Metric)       | 5.2mm  |
| Height H (Imperial)                 | 0.125"   |
| Height H (Metric)                   | 3.2mm  |
| Mounting Hole Diameter D (Imperial) | 0.2"   |
| Mounting Hole Diameter D (Metric)   | 5.1 mm   |
| Mounting Hole Centers (Imperial)    | 1.25"  |

154-00500



|                             |                            |                                  |
|-----------------------------|----------------------------|----------------------------------|
| Material and Specifications |                            |                                  |
|                             | Material                   | Polyamide 6.6 (PA66)             |
|                             | Material Shortcut          | PA66                             |
|                             | Flammability               | UL 94 V2                         |
|                             | Operating Temperature      | -40°F to +185°F (-40°C to +85°C) |
|                             | ROHS Compliant             | Yes                              |
| Logistic and Packaging      |                            |                                  |
|                             | Package Quantity (Metric)  | 100                              |
|                             | Customs Number(Schedule B) | 3926909987                       |