

596-00412



Article Number: 596-00412

Description: Foam Nameplate, 1.25" x 1.25" Button Label With .88" Hole, PET, White, 250/roll

|                                 |                                     |  |
|---------------------------------|-------------------------------------|--|
| Base Data                       | Local Order Number                  | 596-00412  |
|                                 | Type                                | NPLH31X31WH22.5  |
|                                 | Color                               | White (WH)   |
|                                 | Features and benefits               | <ul style="list-style-type: none"> <li>• Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.</li> <li>• Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.</li> <li>• Labels are UV and chemical resistant for long life in an industrial environment.</li> <li>• Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.</li> </ul> |
|                                 | Quantity Per                        | reel   |
|                                 | Product Description                 | Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.   |
|                                 | Technical Description               | Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, White  |
|                                 | Short Description                   | Foam Nameplate, 1.25" x 1.25" Button Label With .88" Hole, PET, White, 250/roll  |
| Product Dimensions              | Length L (Imperial)                 | 1.25"  |
|                                 | Length L (Metric)                   | 31.7mm   |
|                                 | Self adhesive (Yes/No)              | Yes  |
|                                 | Width W (Imperial)                  | 1.25"  |
|                                 | Width W (Metric)                    | 31.7mm   |
|                                 | Height H (Imperial)                 | 1.25"  |
|                                 | Height H (Metric)                   | 31.7mm   |
|                                 | Mounting Hole Diameter D (Imperial) | 0.88"  |
|                                 | Mounting Hole Diameter D (Metric)   | 22.35 mm   |
|                                 | Horizontal Repeat HR (metric)       | 31.7mm   |
| Horizontal Repeat HR (imperial) | 1.25"                               |  |

596-00412



|                             |                                |                                  |
|-----------------------------|--------------------------------|----------------------------------|
| Product Dimensions          | Print Method                   | Thermal transfer                 |
|                             | Vertical Repeat VR (metric)    | 34.92mm                          |
|                             | Vertical Repeat VR (imperial)  | 1.375"                           |
|                             | Width of Liner WL (imperial)   | 1.5"                             |
|                             | Width of Liner WL (metric)     | 38.1mm                           |
| Material and Specifications | Material                       | Polyester (PET)                  |
|                             | Material Shortcut              | PET                              |
|                             | Adhesive                       | Acrylic                          |
|                             | Adhesive Operating Temperature | -40°F to +176°F (-40°C to +80°C) |
|                             | Operating Temperature          | -40°F to +176°F (-40°C to +80°C) |
|                             | ROHS Compliant                 | Yes                              |
|                             | UL Recognized (US)             | Yes                              |
|                             |                                |                                  |
| Logistic and Packaging      |                                |                                  |
|                             | Package Quantity (Imperial)    | 250ft                            |
|                             | Package Quantity (Metric)      | 76.2m                            |
|                             | Customs Number(Schedule B)     | 3919102055                       |
|                             | Labels per Column              | 1                                |
|                             | Labels per Row                 | 1                                |
|                             | Weight (Metric)                | 0.22kg                           |
|                             | Weight (imperial)              | 0.5lbs                           |