HellermannTyton

Article Number: 170-03063



Description: Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel

Base Data		
	Local Order Number	170-03063
	Туре	BSHTTST34SR
	Color	Silver (SR)
	Features and Benefits	 A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. Cuts with ordinary scissors for fast, easy application.
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.48m
	Reel Length (imperial)	100.0ft
	Bundle Diameter Max. (Imperial)	0.687"
	Bundle Diameter Max. (Metric)	17.5mm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	19.1mm
Material and Specifications		
	Material	Glass Fiber (GF)
	Material Shortcut	AL
	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes

170-03063

HellermannTyton

Logi: Pacł	Logistic and Packaging		
		Package Quantity (Imperial)	100ft
		Package Quantity (Metric)	30.48m
		Customs Number(Schedule B)	7019901000
		Weight (imperial)	3.45lbs
		Weight (Metric)	1.57kg