

111-01905



Article Number: 111-01905

Description: High-Temp. Cable Tie, 4" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg

Base Data	
Local Order Number	T18R0HSC2
Type	T18R
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• Heat stabilized cable ties provide excellent resistance to high heat exposures.</li> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	High-Temp. Cable Tie, 4" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	18.0lbs
Minimum Tensile Strength (Metric)	80.0N
Length L (Imperial)	4.0"
Length L (Metric)	100.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.1"
Width W (Metric)	2.45mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm

111-01905



Product Dimensions	Bundle Diameter Max. (Imperial)	0.86"
	Bundle Diameter Max. (Metric)	22.0mm
	Thickness T (Metric)	1.0mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
	Certification/Specification	MIL 53421
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987