MATERIAL	PLATING	NOM. PLATING WT. (GRS)	VENDOR
BeCu	Ag/Cu	Ag=.017; Cu=.0087	FORMCO

PLATE FUSE CLIP 124016-2 AS FOLLOWS:

COMM BRIGHT SILVER .0001" MIN
OVER .00005" MIN COPPER FLASH

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
-	PS001034	CYANIDE COPPER	0.024	LB
-	095400	SILVER PLATE	1.600	TOZ
-	124016-2	FUSE CLIP	1000	EA

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

⬡	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS,-MINIMUM CPK VALUE
⟨ST⟩	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS,-MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

LTR	REVISION	CHK	APD
F	82565D-REVISE &REDRAW TRG 10/15/02		
G	85458D-ADDED CHART 4/19/07 RP		

COPIES TO

1	9	18
2	10	19
3	12	20
4	13	21
5	14	23
6	15	33
7	16	43
8	17	53

MATL SPEC		FINISH
DRW TRG	DATE 10/15/02	SCALE NONE
CHK	DATE	SUPER DRW
APPD	DATE	RAW STK WT LBS/M

TOLERANCE UNLESS OTHERWISE SPECIFIED

TWO PLACE DEC	±.01	FRACTION	±
THREE PLACE DEC	±.005	ANGULAR	±1°

TITLE FUSE CLIP

Littelfuse®
DES PLAINES, ILLINOIS 60016

REVISION G

DRWG. NO. 01230002Z

FINAL

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED