

151-00439

Article Number: 151-00439

Description: Heavy-Duty Mount, .3125" Mounting Hole, 115lb-ft Max Torque, PA66HIRHSUV, Black, 100/pkg



Base Data	Local Order Number	HDM3120HIRC2
	Type	HDM312
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Mount and tie combination makes it easy to service bundles in the field. • Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. • Eliminates the needs for multiple sized fix diameter clamps.
	Quantity Per	bag
	Product Description	This mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.
	Short Description	Heavy-Duty Mount, .3125" Mounting Hole, 115lb-ft Max Torque, PA66HIRHSUV, Black, 100/pkg
Product Dimensions	Length L (Imperial)	1.4"
	Length L (Metric)	36.3mm
	Fixation Method	Screw Mounting and Rivet
	Width W (Imperial)	0.8"
	Width W (Metric)	19.3mm
	Cable Tie Width Max. (Imperial)	0.5"
	Cable Tie Width Max. (Metric)	12.7mm
	Width W2 (Imperial)	0.5"
	Width W2 (Metric)	13.3mm
	Height H (Imperial)	0.7"
	Height H (Metric)	16.7mm
	Height H2 (Imperial)	0.3"
	Height H2 (Metric)	8.0mm
	Mounting Hole Diameter D (Imperial)	0.3"

151-00439



Product Dimensions	Mounting Hole Diameter D (Metric)	7.8 mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSW
	Flammability	UL 94 HB
	Maximum Torque (kgf-cm)	132.5kgf-cm
	Maximum Torque (lbf-ft)	9.583lbf-ft
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces