

Label - EML (26,5X12)R SR - 0816854

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Label, Roll, silver/matt, Unlabeled, Can be labeled with: Thermomark R, Thermomark X, Thermomark S, Mounting type: Adhesive, Lettering field: 26.5 x 12 mm



The figure shows the EML (15X9)R SR product variant

Why buy this product

- A wide range of marker sizes and colors are available for custom designs
- If high-quality ink ribbons are used, the labeling is resistant to solvents and suitable for use even under harsh industrial conditions
- Precise printing quality and good adhesive properties
- The EML ... materials are UL-listed
- The special packaging protects rolls that have already been started from the dirt found in industrial environments
- The EML ... self-adhesive device markers have been specifically developed for marking various types of operating equipment in control, system, and control cabinet engineering

Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 |
| Minimum order quantity | 1 |
| Catalog page | Page 213 (CL2-2011) |
| GTIN |  4 046356 107808 |
| Weight per Piece (excluding packing) | 334.9 GRM |
| Country of origin | GERMANY |

Technical data

General

| | |
|---------------------------------|--------------------------------|
| Length (b) | 26.5 mm |
| Width (a) | 12 mm |
| Color | silver/matt |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Components | free from silicone and halogen |
| Material | Polyester |
| Material | Polyester |
| Number of individual labels | 2500 |

Label - EML (26,5X12)R SR - 0816854

Technical data

General

| | |
|-------------------------------------|---|
| Number of individual labels per row | 3 |
|-------------------------------------|---|

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27149103 |
| eCl@ss 6.0 | 27149103 |

etim

| | |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |

unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Approvals

Certificates

Certification

UL Recognized

Certification EX

Certification submitted

Approval details

| |
|---------------|
| UL Recognized |
|---------------|

Accessories

Accessories

Label - EML (26,5X12)R SR - 0816854

Accessories

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384



Ink ribbon, Length: 300000 mm, Width: 110 mm, Color: black

Marker carriers - CARRIER-EMLP 22 (27X12,5) - 0828985



Marker carriers, black, Unlabeled, Mounting type: Screws, rivets, Diameter: 22 mm, Lettering field: 27 x 12.5 mm
